

# R•O•M Power Cargo Cover

## Technical Specifications



### Standard Features

Flush Track	Power Lock	Door Ajar Switch
Satin Finish	Override Lock	

### Size - Shutter

	Maximum	Minimum
Shutter length	226 "	30"
Shutter width*	76 "	28"
Shutter vertical height**	96 "	19"

\* Doors wider than 50" require a hose bed divider / 1-1/4" below top of opening.

\*\* Maximum vertical height is limited by the opening width. For details see the chart below.

Opening Width	Max. Vertical Height	Opening Width	Max. Vertical Height	Opening Width	Max. Vertical Height
28" to 62"	96"	67"	90"	72"	83"
63 "	95"	68"	88"	73"	82"
64 "	94"	69"	87"	74"	81"
65 "	92"	70"	86"	75"	80"
66 "	91"	71"	85"	76"	79"

### Size – Spiral Assembly

B	Shutter length	30" to 90"	Height = 12.144"	Length = 16.875"
C	Shutter length	90" to 132"	Height = 14.203"	Length = 18.805"
D	Shutter length	132" to 174"	Height = 16.000"	Length = 20.875"
E	Shutter length	174" to 226"	Height = 18.500"	Length = 22.937"

### Weight

Shutter	Approx. 2.10 lbs. per sq. ft.
Spiral Assembly	Approx. 30 lbs. (varies by shutter size)

### Electrical

Motor	30 Amp circuit / 12V minimum	
Lighting	10 Amp circuit / 12V minimum	
Controller Features	Solid state components	Built-in shut off when shutter is obstructed
	Built-in circuit protection	Diagnostic lights for troubleshooting

### Ratings

Maximum load	800 lbs. at center - NOT rated as a walk surface
Water penetration	Minimizes introduction of dirt, dust, water into the compartment
Fire protection	Made of flame-resistant materials