



Technical Bulletin

EXTREME Cargo Tray & Slides

Our Technical Bulletins are provided to inform you of design options, design improvements, standard sizes and changes, different models, applications, installation, operation and maintenance.

FM-7.5-08
Rev G
06-20-11

The R•O•M EXTREME Cargo Tray and Slides were designed to improve functionality while providing corrosion resistance, weight reduction, and easy installation.

Straight pullout models include:

70% extension -1000 lb. load capacity – upper or lower slides

100% extension - 600 lb. load capacity – upper slides

120% extension - 600 lb. load capacity – upper slides

70% extension Dual Directional - 1000 lb. load capacity – upper slides

Released
June 2011

Tilt pullout models include:

90% extension -250 lb. load capacity – upper or lower slides

The tilt angle is approximately twenty-five degrees.

The “**EXTREME Upper Slide**” option allows for a formed tray or other equipment to be attached to the top flanges of the carriage rails. The end user can order a tray from R•O•M or fabricate their own standard size or oversize tray. Deck height for this option is approximately 4”.

The “**EXTREME Lower Slide**” option includes a formed tray that attaches to the bottom flanges of the carriage rails. This option integrates the rails to complete the enclosed tray, and is standard on 70% Straight and 90% Tilt Lower options. Deck height for this option is approximately 1 7/8”. This option is only available on the 70% Straight & 90% Tilt.

External or Internal mounting options are available on all models.

R•O•M Extreme Cargo Tray and Slide models feature a full width pull handle for rapid response applications. The Straight Pullout model incorporates latching in opened and closed positions, including the Dual Directional with latching in the intermediate position, 35% open and 70% open in both directions. The Tilt Pullout model latches only in the closed position. Material compositions are heavy duty aluminum and corrosion resistant zinc plated hardware. Unique heavy duty v-groove bearings eliminate binding for smooth operation.

Please provide this information to your engineering, manufacturing, sales and marketing departments, and to your dealers.

Copyright © 2011 R•O•M Corporation. All Rights Reserved.



These drawings and the information contained herein are the confidential and proprietary intellectual property of R•O•M Corporation and should not be disclosed to any third party without the express prior written consent of R•O•M Corporation.

Base Assembly dimensions are:

Model	Style	Slides	Mount	Load Capacity (lbs)	Base Assembly Width (min / max)	Base Assembly Depth (min / max)
D7U	70% Straight Dual Directional	Upper	External	1000	22-1/2" / 59-1/2"	58" min. 102" max.
			Internal		18-1/2" / 59-1/2"	
S1U	100% Straight	Upper	External	600	22-1/2" / 59-1/2"	20" min. 60" max.
			Internal		18-1/2" / 59-1/2"	
S2U	120% Straight	Upper	External	600	22-1/2" / 72"	29" min. 84" max.
			Internal		18-1/2" / 72"	
S7U	70% Straight	Upper	External	1000	22-1/2" / 59-1/2"	15-1/4" min. 60" max.
			Internal		18-1/2" / 59-1/2"	
S7L	70% Straight	Lower	External	1000	22-1/2" / 59-1/2"	15-1/4" min. 60" max.
			Internal		18-1/2" / 59-1/2"	
T9U	90% Tilt	Upper	External	250	22-1/2" / 59-1/2"	15-1/4" min. 48" max.
			Internal		18-1/2" / 59-1/2"	
T9L	90% Tilt	Lower	External	250	22-1/2" / 59-1/2"	15-1/4" min. 48" max.
			Internal		18-1/2" / 59-1/2"	

Figures 1A & 1B illustrate critical reference dimensions for the UPPER SLIDES option for 70%, 100% and 120% Straight, and 90% Tilt

**FIGURE 1A
(with return)**



**FIGURE 1B
(no return)**

Figures 2A & 2B illustrate critical reference dimensions for the **LOWER SLIDES** option on **70% Straight and 90% Tilt**

FIGURE 2A
(with return)




FIGURE 2B
(no return)




Figure 3 illustrates critical reference dimensions for the **70% Dual Directional** option for **return and no return:**




FIGURE 3